AMENDMENTS TO THE CLAIMS:

This listing of claims will replace all prior listings of claims in the application:

- (Currently Amended) A lever ring for seaming to a body (20) and for receiving a closure layer (1) affixed with an edge by means of portion by sealing and for bridging an inner space of the lever ring, to close the body (20) in a seam-connected position, wherein
 - the lever ring comprises a continuous flat web (3a, 3b, 3e) which radially
 outwardly mergesehanges-into an edge rim (2) of the lever ring, a continuous
 surrounding groove (N1, N2, N3) extending between the edge rim and the flat
 web;
 - (ii) the flat web is suitable for eonnecting anaffixing the edge portion of the closure layer (11) by sealing, and extends at an angle (α1, α2, α3) differing from zero with respect to a plane of the closure layer (1) affixed, that has been connected by such said scaling, at an angle (α1, α2, α3) differing from zero.
- (Currently Amended) A lever ring for seaming to a body (20) and for receiving a closure layer (1) affixed with an edge by means of portion thereof by sealing and for bridging an inner space of the lever ring, to close the body (20) in a seam-connected position, wherein
 - (i) the lever ring comprises a continuous flat web (3a, 3b, 3e) which radially outwardly ehanges continues into an edge rim (2) of the lever ring, a continuous groove (N1, N2, N3) extending between the edge rim and the flat web;

- the flat web extends upwardly inclined from a horizontal plane at an angle (0.2) differing from zero and is provided with an inner curling (4) on its radially inner end so that a closure layer (1) affixed to it by sealing (30)scaled to the flat web and subjected to a pressure force (F) acting vertically to a plane of extension of the closure layer introduces a substantial force component (z) into a scaling seam (30)zone, so that the force component extends in an extension direction of the scaling zone, seam, upon a pressure force (F₀) acting vertically to a plane of extension of the closure layer.
- (Previously Presented) The lever ring according to claim 2, wherein the angle differing from zero is between substantially 10° and substantially 90°.
- 4. (Previously Presented) The lever ring according to claim 2, wherein the angle (α 2) is between substantially 40° and 60°.
- 5. (Previously Presented) The lever ring according to claim 2, wherein the angle (α 2) is between substantially 25° and 35°.
- 6. (Previously Presented) The lever ring according to claim 2, wherein the angle (α 2) is between substantially 80° and 90°.
- (Previously Presented) The lever ring according to claim 2, wherein the angle differing
 from zero extends substantially vertically to the extension of the plane of the closure layer-(4).

U.S. Patent Appln. No. 10/568,617 Attv. Docket No. 60291,000045

8. (Currently Amended) The lever ring according to claim 2, wherein said receivingscaling of the closure layer is a sealing of an edge <u>portion</u> of the closure layer by a sealing <u>strip</u> (30) onin a sealing <u>zone to</u> the flat web (3a, 3b, 3e) which sealing <u>zonestrip</u> extends circumferentially along with the edge rim (2) of the lever ring.

 (Currently Amended) The lever ring according to claim_1-2, wherein the flat web comprises radially inwards an inner curling-(4).

10. (Currently Amended) The lever ring according to claim 2, wherein the closure layer extends over on the inner curling (4) and is deflected (u) so that an edge strip (1b) is formed, which extends at an angle differing from zero, with respect to the a plane of the closure layer (1) in the inner space area of the lever ring.

11. (Previously Presented) The lever ring according to claim 2, wherein the closure layer is formed as a membrane made of one or more materials selected from a group consisting of: plastic, sheet metal, metal foil, and compound foil.

12. (Currently Amended) The lever ring according to claim 2, wherein the sealing <u>zongseam</u> (30) as a strip extending circumferentially has a substantial width on theof extension <u>on</u> of the flat web (3), this, the width being more than half theof a width of the flat web.

- 13. (Currently Amended) The lever ring according to claim 2, wherein the inner curling axially projects above an upper side of the lid rim (2) with an alignment of the flat web (3a) that projects steeply upwards.
- 14. (Currently Amended) The lever ring according to claim 2, wherein the groove (N1+,N2+, N3+) is of a wedge-shaped design with a rounded bottom and is formed between a chuck wall extending towards the <u>surrounding lid rim (2)</u> and the <u>surrounding inclined flat web, (3a, 3b, 3e)</u> that is oriented in an inclined fashion.
- 15. (Previously Presented) The lever ring according to claim 1, wherein the angle differing from zero is between substantially 10° and substantially 90°.
- 16. (Previously Presented) The lever ring according to claim 1, wherein the angle (α 2) is between substantially 40° and 60°.
- 17. (Previously Presented) The lever ring according to claim 1, wherein the angle (α 2) is between substantially 25° and 35°.
- 18. (Previously Presented) The lever ring according to claim 1, wherein the angle (α 2) is between substantially 80° and 90°.
- 19. (Currently Amended) The lever ring according to claim 1, wherein the angle differing from zero extends substantially vertically to the extension of the plane of the closure layer (+).

U.S. Patent Appln. No. 10/568,617 Attv. Docket No. 60291,000045

20. (Currently Amended) The lever ring according to claim 1, wherein said receiving of the closure layer is a sealing of an edge of the closure layer to a circumferential by a scaling strip (30) on the flat web, (3a, 3b, 3e) which sealing strip extends circumferentially.

21. (cancelled)

- 22. (Currently Amended) The lever ring according to claim 1, wherein the closure layer extends over on the inner curling (4) and is thereby deflected (u) so that an edge strip (1b) is formed, which extends at an angle differing from zero, with respect to the plane of the closure layer (1) in the inner space area of the lever ring.
- 23. (Previously Presented) The lever ring according to claim 1, wherein the closure layer is formed as a membrane made of one or more materials selected from a group consisting of: plastic, sheet metal, metal foil, and compound foil.
- 24. (Currently Amended) The lever ring according to claim 1, wherein <u>a the</u>-sealing seam (30) as a strip extending circumferentially has a substantial width on the extension of the flat web (3), this width being more than half of a the width of the flat web.

U.S. Patent Appln. No. 10/568,617 Atty. Docket No. 60291.000045

- 25. (Currently Amended) The lever ring according to claim 1, wherein an the-inner curling at the flat web axially projects above an upper level side of the lid rim (2) with an alignment of the flat web (3a) that projectsing steeply upwards.
- 26. (Currently Amended) The lever ring according to claim 1, wherein the groove (N1, N2, N3) is of a wedge-shaped design with having a rounded bottom and is formed between a chuck wall extending towards the lid rim (2) and the flat web (3a, 3b, 3e) that is oriented in an inclined fashion-extending at an angle differing from zero.